

EMS Marker

Amifast Electronic Markers provide underground identification up to 5 feet. Markers function without an external power source and can be cast directly into enclosure lids.

| ltem # | Marker Depth | Outside Diameter | Inside Diameter | Material | Weight (lbs) | | |
|------------|-----------------|---------------------|--------------------|----------|-----------------|--|--|
| EMS Marker | | | | | | | |
| EMS3 | 3 ft | 4 | 3 3/8 | Wire | .03 | | |
| EMS5 | 5 ft | 4 3/4 | 4 | Wire | .04 | | |



Eye Nut



Eye Nut, 3/4" bolt diameter. Hot dip galvanized.

| Item # | Description | Thread Size | Slot Width | Slot Height | Material | Finish | Weight (lbs) |
|--------|-----------------|-------------|------------|-------------|----------|--------|--------------|
| EN34G | 3/4"-10 Eye Nut | 3/4 | 1 5/8 | 2 3/8 | Steel | HDG | 1.02 |

HDG Hot Dip Galvanized

Copper Grounding Bar



| Item # | Description | Length | Width | Thickness | Screw Size | Material | Weight (lbs) |
|--------|----------------------|--------|-------|-----------|--------------------------------------|----------|--------------|
| CGB | Copper Grounding Bar | 4 5/8 | 1/2 | 1/2 | 1/4"-20 x 3/8 Hex Head Machine Screw | Copper | .37 |